

Lp.	Podstawa	Opis i wyliczenia	j.m.	Poszcz	Razem
		poz.82	mb ob- wodu	44.7000	
				<b>RAZEM</b>	<b>44.7000</b>
84 d.1.5	KNR 2-02 0506-01	Obróbki przy szerokości w rozwinięciu do 25 cm - z blachy ocynkowanej  0.1*(6.37+5.1) 0.1*(3.07*2+3.82)	m <sup>2</sup>  m <sup>2</sup> m <sup>2</sup>	  1.1470 0.9960	
				<b>RAZEM</b>	<b>2.1430</b>
85 d.1.5	KNR 2-02 0506-02	Obróbki przy szerokości w rozwinięciu ponad 25 cm - z blachy ocynkowanej  0.3*(5.1+6.37+2.85*2+3.04*2) 0.3*(3.82) 0.25*(6.37+5.1) 0.25*(3.82+3.07*2)	m <sup>2</sup>  m <sup>2</sup> m <sup>2</sup> m <sup>2</sup>	  6.9750 1.1460 2.8675 2.4900	
				<b>RAZEM</b>	<b>13.4785</b>
86 d.1.5	KNR W-01 0101-09	Przecinanie podłoży betonowych szerokości 5 mm na głębokość 5 cm  6.37+5.1+3.82+3.07*2	m  m	  21.4300	
				<b>RAZEM</b>	<b>21.4300</b>
<b>1.6</b>		<b>WYMIANA STOLARKI OKIENNEJ I DRZWIOWEJ</b>			
87 d.1.6	KNR 4-01 0354-05	Wykucie z muru ościeżnic drewnianych o powierzchni ponad 2 m2  O1 1.6*1.6*10 O2 <del>1.2*1.6*5</del> 1.2*1.6*3= 5,75 O3 1.58*1.4*7 O4 0.57*0.75 O5 2.0*2.35*(36) O10 <del>1.64*2.45*24</del> 1,64*2,45*16= 64,288  D1 1.8*4.72 D2 1.64*3.75 D3 0.9*2.9	m <sup>2</sup>  m <sup>2</sup> m <sup>2</sup> m <sup>2</sup> m <sup>2</sup> m <sup>2</sup>  m <sup>2</sup> m <sup>2</sup> m <sup>2</sup>	  25.6000 5,75 <del>9.6000</del> 15.4840 0.4275 169.2000 64,288 <del>96.4320</del>  8.4960 6.1500 2.6100	
				<b>RAZEM</b>	<b>298.0055</b>
88 d.1.6	KNR 4-01 0354-11	Wykucie z muru podokienników drewnianych wewnętrznych  1,28*3 1,72*16 1.68*10+ <del>1.28*5</del> +1.66*7+0.65+2.08*36+1.92*4+2.56+2.68+ <del>1.72*24</del> +1.92*2+1.28*2	m  m	  157.31 <del>173.6300</del>	  157,31
				<b>RAZEM</b>	<b>-173.6300</b>
89 d.1.6	NNRNKB 202 1025-04	Okna PCV koloru białego z kształtowników z wysokoudarowego PCW  O1 1.6*1.6*10 O2 <del>1.2*1.6*5</del> 1.2*1.6*3= 5,75 O3 1.58*1.4*7 O4 0.57*0.75 O5 2.0*2.35*(36) O10 <del>1.64*2.45*24</del> 1,64*2,45*16= 64,288	m <sup>2</sup>  m <sup>2</sup> m <sup>2</sup> m <sup>2</sup> m <sup>2</sup> m <sup>2</sup>	  25.6000 5,75 <del>-9.6000</del> 15.4840 0.4275 169.2000 64,288 <del>96.4320</del>	      280,7495
				<b>RAZEM</b>	<b>316.7435</b>
90 d.1.6	NNRNKB 202 1025-05	Drzwi zewnętrzne drewniane  D1 1.8*4.72 D2 1.64*3.75 D3 0.9*2.9	m <sup>2</sup>  m <sup>2</sup> m <sup>2</sup> m <sup>2</sup>	  8.4960 6.1500 2.6100	
				<b>RAZEM</b>	<b>17.2560</b>
91 d.1.6	KNR 2-02 0129-02	Obsadzenie prefabrykowanych podokienników  95 73	szt  szt	  73 <del>95.0000</del>	  73
				<b>RAZEM</b>	<b>95.0000</b>
92 d.1.6	kalk. własna	Dostawa parapetów wewnętrznych z płyt okleinowanych  1,28*3 1,72*16 1.68*10+ <del>1.28*5</del> +1.66*7+0.65+2.08*36+1.92*4+2.56+2.68+ <del>1.72*24</del> +1.92*2+1.28*2	m  m	  135.31 <del>173.6300</del>	  135,31
				<b>RAZEM</b>	<b>-173.6300</b>
93 d.1.6	KNR 2-02 0807-07	Wykonywane ręcznie tynki wewnętrzne cementowe kat. IV na ościeżach o szerokości do 20  0.35*(1.7+2.1*2+2.48+2.45*2+1.64*24+2.45*24*2+1.84*2+2.45*2*2+1.25*2+2.45*2*2+1.8+ 4.72*2+1.64+3.75*2+1.25*8+2.35*8*2+2.0*6+2.35*6*2+0.66*2+1.66*2*2+2.0*18+2.35*18*2+ 1.84*2+2.35*2*2+2.6+2.35*2+1.25*4+2.35*4*2+2.0*10+2.35*10*2+2.0*18+2.35*18*2+1.84) 0.3*(1.6*3*15+1.2+1.4*2*3+1.58+1.4*2+1.05+1.4*2+1.2*5+1.6*10+1.58*7+1.4*14+0.57+0.75*2) 0.76*(0.9+2.9*2)	m <sup>2</sup>  m <sup>2</sup> m <sup>2</sup> m <sup>2</sup>	  233.2330  43.3680 5.0920	
				<b>RAZEM</b>	<b>281.6930</b>
94 d.1.6	KNP RPDE 71- 191a	Osadzanie kątownika z wyszpaldowaniem na głębokości 5 cm	m		